



Digital Guardian



Model No.
LC-JLC-RQ-A

Alarm Light Control System

Function of Automatic Light Control System

Automatic Light Control system integrated with Intruder Alarm system, If any alarm triggered in non-working hours, the lights will be ON automatically and will be get clear view in CCTV also

Component used in Automatic Light Control system

1. DC 12 Volt Relay for controlling DC voltage from the Alarm Control Panel Output
2. AC 220 Volt Conductor for controlling AC voltages from the lights ON/OFF switch
3. Encloser PVC box

Specifications Model		LC-JLC-RQ-A
Terminal Layout		3Z
Contact Capacity	AC	10A 250V
	DC	10A 30V
Contact Resistance (mΩ)		≤50mΩ
Insulation Resistance (mΩ)		≥500mΩ
Dielectric Strength	BOC	1500VAC
	BCC	1500VAC
Coil Nominal Voltage	AC	6 to 380V
	DC	6 to 220V
Coil Nominal Power	AC	≤2.8VA
	DC	≤1.6W
Electric Life (OPS)		105
Mechanical Life (OPS)		107
Operating Temperature(°C)		-40~+60
Weight(g)		≤80
Mounting Methods		Outlet

Mailing Address

VOSTOK Trading L.L.C,
304, 3rd Floor, Al Tawhidi Building,
Khaled Bin Waleed Road,
P.O. Box: 27106 - Dubai,
UNITED ARAB EMIRATES.

Contact Details

Tel: (+971 4) 3558816
Fax: (+971 4) 3558817

Email : sales1@digitalgardian.com /
sales2@digitalgardian.com /